



Cinelite 1000W

LAMPHEAD CONTENTS

- Lamp Housing without Bulb (purple grey color)
- 4-leaf Rotatable Barndoor with Safety Wire
- Wire Guard
- Stirrup with Ø16mm (5/8 in.) Socket
- Inlet Cable 3m (10 ft.)
- In-Line Switch
- Accessory Holder

Requires Lamp Bulb

Cinelite 1000W

SPECIFICATIONS

Identity No.	L01000TO
	L0100ATO (with Accessory Holder)
Capacity	1,000W
Voltage	240V or 120V
Lamp Type	P2/35 1000W 230V or DXW 1000W 120V
Color Temp.	3200K
Lamp Holder	R7s
Stirrup	Ø16mm (5/8 in.) Socket
Class	1
Max. Surface Temp.	220 °C
Max. Ambient Temp.	45 °C
Min. Distance to Illuminated Object	1.5 m
Min. Distance to Flammable Object	0.5 m
Operating Range	+45° - 0° - -45°
Weight (Lamphead)	1.5 kg

ACCESSORIES

4-leaf Rotatable Barndoor

Set of 4 Scrims Ø191mm (7-1/2 in.) :


Full Single, Full Double, Half Single, Half Double

Scrim Bag

Safety Wire (for Barndoor)

Accessory Holder

PHOTOMETRIC DATA



	2m	4m	6m
Spot (40°)			
Lux	9292	2323	1032
Beam Ø	1.46 m	2.91 m	4.37 m
Flood (89°)			
Lux	2929	732	325
Beam Ø	3.93 m	7.86 m	11.79 m

DIMENSIONS (mm)

