

Cinelite 650W

SPECIFICATIONS

Identity No.	L00650TO
	L0065ATO (with Accessory Holder)
Capacity	650W / 600W / 500W
Voltage	240V or 120V or 100V
Lamp Type	DYR650W 230V or DYS600W 120V or JCD500WCC 100V
Color Temp.	3200K
Lamp Holder	GY9.5
Stirrup	Ø16mm (5/8 in.) Socket
Class	1
Max. Surface Temp.	220 °C
Max. Ambient Temp.	45 °C
Min. Distance to Illuminated Object	1 m
Min. Distance to Flammable Object	0.1 m
Operating Range	+45° - 0° - -45°
Weight (Lamphead)	1.5 kg



Cinelite 650W

LAMPHEAD CONTENTS


- Lamp Housing without Bulb (purple grey color)
- 4-leaf Rotatable Barndoor with Safety Wire
- Wire Guard
- Stirrup with Ø16mm (5/8 in.) Socket
- Inlet Cable 3m (10 ft.)
- In-Line Switch
- Accessory Holder

Requires Lamp Bulb

ACCESSORIES

- 4-leaf Rotatable Barndoor
- Set of 4 Scrims Ø127mm :
Full Single, Full Double, Half Single, Half Double
- Scrim Bag
- Safety Wire (for Barndoor)
- Accessory Holder

PHOTOMETRIC DATA



	2m	4m	6m
Spot (27.4°)			
Lux	3172	793	352
Beam Ø	0.97 m	1.95 m	2.93 m
Flood (59°)			
Lux	1428	357	159
Beam Ø	2.27 m	4.53 m	6.80 m

DIMENSIONS (mm)

