

ELECTRONIC BALLAST V3

4kW/2.5kW (Multi-Voltage)



4kW/2.5kW V3 (Multi-Voltage)

SPECIFICATIONS	(1000Hz)	(300Hz)
Identity No.	B042PDK3 (1000Hz, DMX) B042PNK3 (1000Hz)	B042PDX3 (300Hz, DMX) B042PNX3 (300Hz)
Max. Power	4,400VA	4,400VA
Input Voltage	90 - 125V AC 180 - 250V AC	90 - 125V AC 180 - 250V AC
Input Current	24 - 18A @ 180 - 250V AC 49 - 35A @ 90 - 125V AC	24 - 18A @ 180 - 250V AC 49 - 35A @ 90 - 125V AC
Frequency	50Hz or 60Hz	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 1000Hz (High Speed)	60Hz (Silent) 75Hz (Flicker Free) 300Hz (High Speed)
Power Factor	0.99 (PFC)	0.99 (PFC)
Efficiency	91% (PFC)	91% (PFC)
Dimming Control	55%	55%
Fusing	100A	100A
No-load Voltage	360V	360V
Max. Ambient Temp.	50 °C	50 °C
Class / IP Rating	1 / IP 22	1 / IP 22
Weight	21.7kg	21.7kg

DIMENSIONS (mm)

