

ELECTRONIC BALLAST V3

2500W (Multi-Voltage)



2500W V3 (Multi-Voltage)

SPECIFICATIONS	(1000Hz)	(300Hz)
Identity No.	B025PEK3 (1000Hz, DMX) B025PNK3 (1000Hz)	B025PEX3 (300Hz, DMX) B025PNX3 (300Hz)
Max. Power	2,750VA	2,750VA
Input Voltage	90 - 125V AC 180 - 250V AC	90 - 125V AC 180 - 250V AC
Input Current	15 - 11A @ 180 - 250V AC 31 - 22A @ 90 - 125V AC	15 - 11A @ 180 - 250V AC 31 - 22A @ 90 - 125V AC
Frequency	50Hz or 60Hz	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 1000Hz (High Speed)	60Hz (Silent) 75Hz (Flicker Free) 300Hz (High Speed)
Power Factor	0.99 (PFC)	0.99 (PFC)
Efficiency	91% (PFC)	91% (PFC)
Dimming Control	55%	55%
Fusing	50A	50A
No-load Voltage	360V	360V
Max. Ambient Temp.	50 °C	50 °C
Class / IP Rating	1 / IP 22	1 / IP 22
Weight	14kg	14kg

DIMENSIONS (mm)

