

ELECTRONIC BALLAST V3

800W/575W
(Multi-Voltage)



800W/575W V3 (Multi-Voltage, 1000Hz)

SPECIFICATIONS

Identity No.	B008PEK3 (1000Hz, DMX) B008PNK3 (1000Hz)
MaMax. Power	880VA
Input Voltage	90 - 125V AC 180 - 250V AC
Input Current	5 - 4A @ 180 - 250V AC 10 - 7A @ 90 - 125V AC
Frequency	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 1000Hz (High Speed)
Power Factor	0.98 (PFC)
Efficiency	87% (PFC)
Dimming Control	55%
Fusing	25A
No-load Voltage	360V
Max. Ambient Temp.	50 °C
Class / IP Rating	1 / IP 22
Weight	7.4 kg

800W/575W V3 (Multi-Voltage, 300Hz)

SPECIFICATIONS

Identity No.	B008PEX3 (300Hz, DMX) B008PNX3 (300Hz)
Max. Power	880VA
Input Voltage	90 - 125V AC 180 - 250V AC
Input Current	5 - 4A @ 180 - 250V AC 10 - 7A @ 90 - 125V AC
Frequency	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 300Hz (High Speed)
Power Factor	0.98 (PFC)
Efficiency	87% (PFC)
Dimming Control	55%
Fusing	25A
No-load Voltage	360V
Max. Ambient Temp.	50 °C
Class / IP Rating	1 / IP 22
Weight	7.4 kg

DIMENSIONS (mm)

