

ELECTRONIC BALLAST V3

800W/575W

(Multi-Voltage)



800W/575W V3 (Multi-Voltage)

| SPECIFICATIONS | (1000Hz) | (300Hz) |
|--------------------|---|--|
| Identity No. | B008PEK3 (1000Hz, DMX) B008PNK3 (1000Hz) | B008PEX3 (300Hz, DMX) B008PNX3 (300Hz) |
| Max. Power | 880VA | 880VA |
| Input Voltage | 90 - 125V AC 180 - 250V AC | 90 - 125V AC 180 - 250V AC |
| Input Current | 5 - 4A @ 180 - 250V AC 10 - 7A @ 90 - 125V AC | 5 - 4A @ 180 - 250V AC 10 - 7A @ 90 - 125V AC |
| Frequency | 50Hz or 60Hz | 50Hz or 60Hz |
| Output Mode | 60Hz (Silent) 75Hz (Flicker Free) 1000Hz (High Speed) | 60Hz (Silent) 75Hz (Flicker Free) 300Hz (High Speed) |
| Power Factor | 0.98 (PFC) | 0.98 (PFC) |
| Efficiency | 87% (PFC) | 87% (PFC) |
| Dimming Control | 55% | 55% |
| Fusing | 25A | 25A |
| No-load Voltage | 360V | 360V |
| Max. Ambient Temp. | 50 °C | 50 °C |
| Class / IP Rating | 1 / IP 22 | 1 / IP 22 |
| Weight | 7.4kg | 7.4kg |

DIMENSIONS (mm)

